



Solar compact kit

Pre-assembled solar package

- Pre-assembled circulation unit with: 1/2" safety valve, flow meter with flow regulator, system fill and drain valves, shut-off valve and pressure gauge set, solar circulator, shut-off valve, solar electronic controller, expansion tank for 18-lt solar circuit
- The solar controller manages solar circuit temperature through tank and collector probes (1 PT1000 probe + 1 NTC) and features autodiagnosics
- Double coil storage tank, 200 or 300 litres
- SOLEXTECH V 2.1 flat solar collector included with Models ST 200 H / ST 300 H. Solar-keymark certification (EN 12975). 22 mm diameter connection, compression type
- Models BL 200 / BL 300 are without solar collectors (omoboblock only)
- Lodging for electrical heating element, 1" 1/2 fitting

Code	Model
OXGU1MXD	Solar compact kit ST 200 H
OXDTOMXA	Solar compact kit BL 200
OXGU2NXD	Solar compact kit ST 300 H
OXDTONXA	Solar compact kit BL 300

MODEL		ST 200 H	BL 200	ST 300 H	BL 300
Storage tank: ERP Class		C	C	C	C
Storage tank: useful volume	l	196	196	273	273
Storage tank: heat loss	W	67	67	85	85
Solar control unit ECOTRONIC HITECH	n	1	1	1	1
Collector: SOLEXTECH V 2.1	n	1	not supplied	2	not supplied
Collector: overall gross surface / overall effective surface	m ²	2,09 / 1,96	-	4,18 / 3,92	-

Complementary accessories

ASSEMBLY FRAMES FOR SLOPED ROOF	
076239X0	COMPLETE FRAME for no. 1 collector (*)
076240X0	COMPLETE FRAME for no. 2 collectors (*)

(*) In case of more than two collectors, use several kits in combination

FASTENING BRACKETS FOR SLOPED ROOF	
076241X0	Kit 4 brackets for pantiles/tiles (**)
076242X0	Kit 4 universal brackets (**)

(**) Use 1 "Bracket kit" for each "Complete frame kit for pitched roof"

ASSEMBLY FRAMES FOR FLAT ROOF	
076235X0	BASE KIT to be used for 1 collector mod. 2.1 V
076237X0	EXTENSION KIT to be used for each collector (mod. 2.1 V) additional to the first one

HYDRAULIC ACCESSORIES	
Z308904000	Premixed solar fluid PROSUN TP - 2 x 5 kg
Z308904010	Premixed solar fluid PROSUN - 25 kg
0YDI0KX0	Premixed solar fluid PROSUN PLUS -27°C - 25 kg
013002X0	Thermostatic mixer connections 1/2"
072293X0	Purge valve (de-aerator) for the solar circuit