

EU type examination certificate
EU-Baumusterprüfbescheinigung

CE-0085DN0528

Product Identification No.
 Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EU Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
Distributor <i>Vertreiber</i>	Ferrolì S.p.A. Via Ritonda 78A, I-37047 San Bonifacio (VR)
Product Category <i>Produktart</i>	Water heaters: Gas instantaneous water heater (1401)
Product description <i>Produktbezeichnung</i>	Wall-mounted instantaneous water heater with integrated gas burner in modulating operation method and with enclosed combustion chamber
Model <i>Modell</i>	LAMBORGHINI CALORECLIMA ESTORIL ...
Countries of Destination <i>Bestimmungsländer</i>	AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR
Test reports <i>Prüfberichte</i>	Supplement test: K 3264 2023 E3 from 15.05.2023 (TRG) Supplement test: K 3264 2023 E4 from 15.05.2023 (TRG) Supplement test: K 3264 2023 B5 from 15.05.2023 (TRG)
Test basis <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN EN 26 (01.08.2015) DVGW CERT ZP 3100-20 (01.12.2022)
Date of Expiry / File No. <i>Ablaufdatum / AZ</i>	01.09.2032 / 23-0207-GER



70028-04-A-DE

07.06.2023 Kir B-1/2

Date, Issued by, Sheet, Head of Certification Body
 Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



DVGW CERT GmbH - notified by the government of the Federal Republic of Germany and officially registered by the European Commission for conformity assessment of gas appliances

DVGW CERT GmbH – von der Deutschen Bundesregierung benannte und von der Europäischen Kommission offiziell registrierte Stelle für die Konformitätsbewertung von Gasgeräten

DVGW CERT GmbH
 Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
 53123 Bonn

Tel. +49 228 91 88 - 888
 Fax +49 228 91 88 - 993

www.dvgw-cert.com
 info@dvgw-cert.com

Type Typ	Technical Data Technische Daten	Remarks Bemerkungen
ESTORIL 10	Heat input (Hi): 4,0...19,7 kW	
ESTORIL 12	Heat input (Hi): 4,0...23,0 kW	
ESTORIL 15	Heat input (Hi): 4,0...29,7 kW	
ESTORIL 17	Heat input (Hi): 4,0...33,0 kW	

Hints of Utilization /Remarks

Verwendungshinweise / Bemerkungen

Flue types B32, C12, C22, C32, C42, C52, C62, C82, C92: according to installation manual with flue system of Groppalli (approval no. 2592-CPR-0005)

Additionally tested appliance categories, supply pressures and countries of destination:

AL: II2H3B/P, II2R3R; 20 mbar; 30 mbar
 AT: II2H3B/P; 20 mbar; 50 mbar
 BE: II2E(S)3P, II2E(R)3P; 20/25 mbar; 37 mbar
 BG: II2H3B/P, II2R3R; 20 mbar; 30, 37, 50 mbar
 CH: II2H3B/P, II2H3P; 20 mbar; 50 mbar
 CY: II2H3B/P; 20 mbar; 30 mbar
 CZ: II2H3B/P, II2H3P, II2R3R; 20 mbar; 30, 37, 50 mbar
 DE: II2E3B/P, II2R3R, II2ELL3B/P; 20 mbar; 50 mbar
 DK: II2H3B/P, II2R3R; 20 mbar; 30 mbar
 EE: II2H3B/P, II2R3R; 20 mbar; 30 mbar
 ES: II2H3P, II2R3R; 20 mbar; 37 mbar
 FI: II2H3B/P; 20 mbar; 30 mbar
 FR: II2Er3P, II2R3R, II2Esi3P; 20/25 mbar; 37 mbar
 GB: II2H3P; 20 mbar; 30 mbar
 GR: II2H3B/P, II2R3R, II2H3P; 20 mbar; 37 mbar
 HR: II2H3B/P, II2H3P; 20 mbar; 30, 50 mbar
 HU: II2H3B/P, II2R3R; 20 mbar; 30, 37, 50 mbar
 IE: II2H3P; 20 mbar; 30, 37 mbar
 IS: II2H3B/P; 20 mbar; 30 mbar
 IT: II2H3B/P, II2HM3B/P, II2R3R, II2H3P; 20 mbar; 30, 37 mbar
 LT: II2H3B/P, II2H3P; 20 mbar; 30 mbar
 LU: II2H3B/P, II2R3R; 20 mbar; 30, 37, 50 mbar
 LV: II2H3B/P, II2R3R; 20 mbar; 30, 37, 50 mbar
 NL: II2EK3B/P; 20/25 mbar; 30 mbar
 NO: II2H3B/P, II2R3R; 20 mbar; 30 mbar
 MT: II2H3B/P, II2R3R; 20 mbar; 30, 37, 50 mbar
 MK: II2H3B/P, II2R3R; 20 mbar; 30, 37, 50 mbar
 PL: II2ELwLs3B/P, II2E3B/P; 13 mbar; 20 mbar; 30 mbar
 PT: II2H3P, II2R3R; 20 mbar; 37 mbar
 RO: II2H3B/P, II2H3P; 20 mbar; 30 mbar
 SE: II2H3B/P; 20 mbar; 30 mbar
 SI: II2H3B/P, II2R3R; 20 mbar; 30 mbar
 SK: II2H3B/P; 20 mbar; 30 mbar
 TR: II2H3B/P; 20 mbar; 30 mbar

In non-EU countries, the conformity approval will only be accepted once the Gas Appliance Regulation EU/2016/426 will be transferred into national law.

The instantaneous water heater are qualified for the addition of up to 20 vol.-% hydrogen to natural gas (G20) as burning gas according to DVGW CERT ZP 3100-20.

