

C € 0085



EU type examination certificate

EU-Baumusterprüfbescheinigung

CE-0085CT0650

Product Identification No.
Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EU Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
Distributor <i>Vertreiber</i>	Ferrol S.p.A. Via Ritonda 78A, I-37047 San Bonifacio (VR)
Product Category <i>Produktart</i>	Boilers with flue systems: Condensing combi water heater (3204)
Product description <i>Produktbezeichnung</i>	Condensing combi water heater optional also as condensing water heater
Model <i>Modell</i>	LAMBORGHINI CALORECLIMA ALHENA TECH/IDOLA S HYBRID...
Countries of Destination <i>Bestimmungsländer</i>	AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR
Test reports <i>Prüfberichte</i>	Supplement test: K 3026 2025 E26 from 04.08.2025 (TRG) Supplement test: K 3026 2025 B27 from 04.08.2025 (TRG)
Test basis <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN EN 15502-1 (01.08.2024) DIN EN 15502-2-1 (01.07.2025) DVGW CERT ZP 3100-20 (03.04.2025)
Date of Expiry / File No. <i>Ablaufdatum / AZ</i>	14.06.2031 / 25-0200-GER

70028-04-A-DE

19.01.2026 Cz B-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH - notified by the government of the Federal Republic of Germany and officially registered by the European Commission for conformity assessment of gas appliances

DVGW CERT GmbH – von der Deutschen Bundesregierung benannte und von der Europäischen Kommission offiziell registrierte Stelle für die Konformitätsbewertung von Gasgeräten

DVGW CERT GmbH
Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 9188-888
info@dvgw-cert.com
www.dvgw-cert.com

Appliance Categories <i>Geräte kategorien</i>	Supply Pressures <i>Versorgungsdrücke</i>	Countries of Destination <i>Bestimmungsländer</i>	Remarks <i>Bemerkungen</i>
I2ELwLs	20,20,13 mbar	PL	
I2H	20 mbar	CZ, ES, GR, NL	
I3B/P	30 mbar	BE, PT	
I3B/P	50 mbar	DE, GR	
I12E+3+	20/25, 28-30/37 mbar	BE, FR	
I12E+3B/P	20/25, 37 mbar	FR	
I12E+3P	20/25, 37 mbar	BE	
I12E3B/P	20, 50 mbar	DE	
I12E3B/P	20, 30 mbar	PL	
I12EK3B/P	25, 30 mbar	NL	
I12ELL3B/P	20, 50 mbar	DE	
I12ELwLs3B/P	20,20,13, 30 mbar	PL	
I12H3+	20, 28-30/37 mbar	CH, CY, CZ, ES, GB, GR, IE, IT, LT, PT, SI, SK	
I12H3+	20, 30/37 mbar	TR	
I12H3B/P	20, 30 mbar	CY, CZ, DK, EE, FI, HR, HU, IS, IT, LT, NO, RO, SE, SI, SK	
I12H3B/P	20, 37 mbar	HR, LV, TR	
I12H3B/P	20, 50 mbar	AT, CH, GR, LU, SK	
I12H3P	20, 37 mbar	ES, GB, IE, PT	
I12HM3+	20, 28-30/37 mbar	IT	
I12HM3B/P	20, 30 mbar	IT	
I12HM3B/P	20, 37 mbar	IT	
I12HM3P	20, 30 mbar	IT	
I12HM3P	20, 37 mbar	IT	
I12HS3B/P	25, 30 mbar	HU	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
...ALHENA TECH 24 C	Nominal heat output: 2,8...24,5 kW Heat input (Hi): 2,9...25,0 (DHW.: ...25,0) kW	
...ALHENA TECH 28 C/K 50	Nominal heat output: 2,8...28,0 kW Heat input (Hi): 2,9...28,5 (DHW.: ...28,5) kW	
...ALHENA TECH 34 C/K 50 / B 34 K 50	Nominal heat output: 2,8...34,0 kW Heat input (Hi): 2,9...34,7 (DHW.: ...34,7) kW	
...ALHENA TECH 28 H	Nominal heat output: 2,8...28,0 kW Heat input (Hi): 2,9...28,5 kW	
...ALHENA TECH 34 H/B 34	Nominal heat output: 2,8...34,0 kW Heat input (Hi): 2,9...34,7 kW	
...ALHENA TECH 45 H	Nominal heat output: 6,3...42,9 kW Heat input (Hi): 6,4...43,8 kW	
...IDOLA S HYBRID 28C 3.2 UI 6/10	Nominal heat output: 2,8...28,0 kW Heat input (Hi): 2,9...28,5 (DHW.: ...28,5) kW	
...IDOLA S HYBRID 28H 3.2 UI 6/10	Nominal heat output: 2,8...28,0 kW Heat input (Hi): 2,9...28,5 kW	

Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>
...C; ...C...	condensing combi water heater
...H	condensing water heater
...K 50	with hot water storage tank (50 liters)
...B	floor standing

Hints of Utilization /Remarks

Verwendungshinweise / Bemerkungen

Electrical data: 230 V AC, 50 Hz

Flue types B23, B33, C13, C13x, C23, C33, C43, C43x, C53, C53x, C63, C63x, C83, C93, C93x, C(10)3, C(10)3x, C(11)3, C(11)3x, C(12)3, C(13)3, C(14)3, C(14)3x, C(15)3, C(15)3x: according to installation manual with flue system of Groppalli (2592-CPR-001)

Approved appliance categories, supply pressures and countries of destination: AL, MK: I12E3B/P (20, 50 mbar); BG, MT: I12H3B/P (20, 30 mbar); ES, FR, PT: I2N (20 mbar); FR: I2N (25 mbar); FR: I2H (20/25); BE, SI: I2N (20 mbar); ES, IE: I3B (30 mbar); NL: I12L3B/P (25, 30); DE, LU, RO: I2E (20 mbar)

In non-EU countries, the conformity approval will only be accepted once the Gas Appliance Regulation EU/2016/426 will be transferred into national law.

The boilers are qualified for the addition of up to 20 vol.-% hydrogen to natural gas (G20) as burning gas.